



INTRINSICALLY SAFE BARRIERS

HOW TO ORDER:

Intrinsically Safe Barrier, Stahl Single Channel,
9001/01-280-100-10

Intrinsically Safe Barrier, Stahl Single Channel,
9001/01-280-075-10

Intrinsically Safe Barrier, Stahl Dual Channel,
9002/13-280-110-00

Intrinsically Safe Barrier, Crouse Dual Channel,
GHG1110000W2427

SPECIFICATIONS:

Stahl Single Channel, 9001/01-280-100-10

Positive potential
 $V_{oc} = 28 \text{ VDC}$, $I_{sc} = 100 \text{ mA}$
Internal resistance = 302 ohm

Stahl Single Channel, 9001/01-280-075-10

Positive potential
 $V_{oc} = 28 \text{ VDC}$, $I_{sc} = 68.5 \text{ mA}$
Internal resistance = 440 ohm

Stahl Dual Channel, 9002/13-280-110-00

Positive potential
 $V_{oc} = 31 \text{ VDC}$, $I_{sc} = 109 \text{ mA}$
280 ohm + 1 VDC

Crouse Dual Channel, GHG1110000W2427

Positive potential
 $V_{oc} = 26.3 \text{ VDC}$, $I_{sc} = 102 \text{ mA}$
286 ohm + .7 VDC

WIRING

HOW TO ORDER:

Wire, 18 AWG 4-Conductor, Belden 8489
Part number: 8489

Wire, 20 AWG 4-Conductor, Belden 8484
Part number: 8484

SPECIFICATIONS:

4 conductor, unsheilded
18 or 20 AWG, stranded (19x30)
Insulation - PVC - Polyvinyl Chloride
Jacket - PVC - Polyvinyl Chloride

PRINTER RIBBON

Used with Electronic Sensors, Inc. printer model 5011-03.

HOW TO ORDER:

Ribbon 5011-10

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Electronic Sensors, Inc.
2063 S Edwards St
Wichita, KS 67213

Rev. 11/09

Phone: 316-267-2807
Toll Free: 800-886-2511
Fax: 316-267-2819
Email: leveldevil@leveldevil.com
Home Page: www.leveldevil.com


Level Devil®
Bulk Inventory Management Solutions